



	Fresh Water	Pool Water	Sea Water	220-240 V	400 V	110-120 V	50 Hz	60 Hz	12 V AC	24 V DC	DMX	DMX/ RDM	Plug and Spray
Extension cable hybrid													

EXTENSION CABLE HYBRID 3.0m /01 AND 7.5m /01

OASE Extension cable hybrid are designed for underwater applications as well.

The Extension cable hybrid (data+ power supply) are suitable for:

- ProfiLux LED 110 /DMX/02 (56267)
- ProfiPlane LED 110 /DMX/02 (56298)
- ProfiLux LED 320 /DMX/02 (50717)
- ProfiRing LED 320 /DMX/02 (50718)
- ProfiPlane LED 320 /DMX/02 (50719)
- ProfiLux LED Spot 1500 /DMX/02 (56388)
- ProfiLux LED Flood 1500 /DMX/02 (56391)

Only one extension cable can be used per LED unit.

Product characteristics at a glance

- Extension cable hybrid 3.0 m or 7.5 m long with connector
- Female / male connections
- IP 68 protection
- 4-core shielded



Extension cable hybrid / 3.0 m /01



Scope of delivery

- 4 x screw M5
- 1 x cable
- 1 x connector
- 1 x gland seal

Accessories (must be ordered separately)

Power splice 20	57648
-----------------	-------

Extension cable hybrid	3.0 m /01	7.5 m /01
<p>Male</p> <p>Female</p>		
Extension cable hybrid	3.0 m /01	7.5 m /01
Length [m]	3.0	7.5
Cable diameter [mm ²]	4 x 0.34	2 x 1; 2 x 0.24
Weight [kg]	0.38	0.75
Order no.	50728	56403