

01 Specs	SplashCan		22.11.20 MH	Project																																				
01Title			VS.01	No.																																				
Item / No.	Description / Quantity / Unit		Unit price	total price																																				
01.1 Position	Description: Stainless steel mounting niche suited for Splash Deck Fountains and the integration of SplashKit products or sim. Installation and operation in fresh-, pool- and seawater.* Technical data: Dimensions (ØxH): 365 x 439 [mm] Material: PET, UV-stabilised, Stainless steel 1.4301 (AISI 304) Weight: 3 kg Connections cable gland /perimeter 4 x 1 " cable gland /bottom 4 x 1 " water inlet/bottom 1" drainage / bottom 2" * on special demand only <table><tr><th colspan="4">water-quality-matrix</th></tr><tr><th></th><th>Freshwater</th><th>Poolwater</th><th>Seawater</th></tr><tr><td>PH.Value</td><td>7,2 -7,6</td><td>7,2 -7,6</td><td>8</td></tr><tr><td>Hardness</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>20 -30 ° DH; 356 - 534 ppm CaCo3</td></tr><tr><td>Free Chlorine</td><td>< 0,3 mg/l; < 0,036 moz/gal</td><td>0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td><td>< 0,3 mg/l; < 0,036 moz/gal</td></tr><tr><td>Chlorine concentration</td><td>< 250 mg/l; < 30,28 moz/gal</td><td>< 200 mg/l; < 24,2 moz/gal</td><td><=22000 mg/l; <=2664 moz/gal</td></tr><tr><td>Salinity</td><td>n. d.</td><td>n. d.</td><td><= 4%; <= 40.000 ppm</td></tr><tr><td>Total Dry Residue</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 250mg/l; < 30,28 moz/gal</td></tr><tr><td>Temperature</td><td>4 -35° C; 39 - 95 ° F</td><td>4 -30° C; 39 - 86 ° F</td><td>4 - 20 ° C; 39 - 68 ° F</td></tr></table>		water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																								
	Freshwater	Poolwater	Seawater																																					
PH.Value	7,2 -7,6	7,2 -7,6	8																																					
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																					
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																					
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																					
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																					
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																					
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																					
Supply and delivery according to manufacturer specifications. Product / proof of delivery: SplashCan Art. 77881 OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800 (or equivalent) Entered by the bidder																																								