

01 Specs	Comet 5 - 8 Silver		01.09.16 AO	Project No.																																				
01Title			VS.02																																					
Item / No.	Description / Quantity / Unit		Unit price	Total price																																				
01.1 Position	Description: Clear stream nozzle made of chromed and nickel plated brass. Installation and operation in freshwater.* Technical data: Dimensions (Ø x H): 28 x 87 [mm] Material: double coated brass Weight: 0,13 kg Effect height: 0,5 - 4,0 [m] Nozzle diameter at orifice: 8 mm Adjustable angular range: 15° Water-level independent: yes Double nipple: Material: double coated brass Integrated flow rectifier: yes Connecting thread (Outside thread): G1/2 Union nut: Material: double coated brass Chamfered: yes Connecting thread (Inner thread): G1/2 Wrench size: AF24 * <table><tr><th colspan="4">water-quality-matrix</th></tr><tr><th></th><th>Freshwater</th><th>Poolwater</th><th>Seawater</th></tr><tr><td>PH.Value</td><td>7,2 -7,6</td><td>7,2 -7,6</td><td>8</td></tr><tr><td>Hardness</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>20 -30 ° DH; 356 - 534 ppm CaCo3</td></tr><tr><td>Free Chlorine</td><td>< 0,3 mg/l; < 0,036 moz/gal</td><td>0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td><td>< 0,3 mg/l; < 0,036 moz/gal</td></tr><tr><td>Chlorine concentration</td><td>< 250 mg/l; < 30,28 moz/gal</td><td>< 200 mg/l; < 24,2 moz/gal</td><td><=22000 mg/l; <=2664 moz/gal</td></tr><tr><td>Salinity</td><td>n. d.</td><td>n. d.</td><td><= 4%; <= 40.000 ppm</td></tr><tr><td>Total Dry Residue</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 250mg/l; < 30,28 moz/gal</td></tr><tr><td>Temperature</td><td>4 -35° C; 39 - 95 ° F</td><td>4 -30° C; 39 - 86 ° F</td><td>4 - 20 ° C; 39 - 68 ° F</td></tr></table> Supply and delivery according to manufacturer specifications. Product / proof of delivery: Comet 5 - 8 Silver Art. 50762 OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800 (or equivalent) Entered by the bidder		water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																								
	Freshwater	Poolwater	Seawater																																					
PH.Value	7,2 -7,6	7,2 -7,6	8																																					
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																					
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																					
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																					
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																					
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																					
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																					