

01 Specs 01Title	LED XL EasyFit 10	15.7.20 MH VS.01	Project No.																																				
No / Art.	Description / Quantitiy / Unit	Unit price	Total price																																				
01.1 Position	<p>Description: Inlet necessary for nozzle installation into ProfiRing / ProfiPlane LED XL RGB Spot /DMX/02 consisting of: inlet , O-ring , counter part</p> <p>Suitable for dry and wet application.</p> <p>Environmental conditions for dry application: Temerature range for dry application: +4° - +35°C</p> <p>Environmental conditions for wet applications (water quality) Installation and operation in fresh-, pool- and seawater.*</p> <p>Technical data: Dimensions (Ø x H): 54.4 x 32.6 [mm] Material: Stainless steel 1.4404 (AISI 316) / plastic Total weight: 0.15 kg Protection class: IP 68 / 4m max. Nozzle connection/ Inner thread G1</p> <p>*</p> <table><tr><th colspan="4">water-quality-matrix</th></tr><tr><th></th><th>Freshwater</th><th>Poolwater</th><th>Seawater</th></tr><tr><td>PH.Value</td><td>7.2 -7.6</td><td>7,2 -7,6</td><td>8</td></tr><tr><td>Hardness</td><td>8 -15 ° DH;</td><td>8 -15 ° DH;</td><td>20 -30 ° DH;</td></tr><tr><td>Free Chlorine</td><td>< 0.3 mg/l;</td><td>0.3 -0.6 mg/l;</td><td>< 0.3 mg/l;</td></tr><tr><td>Chlorine</td><td>< 250 mg/l;</td><td>< 200 mg/l;</td><td><=22000 mg/l;</td></tr><tr><td>Salinity</td><td>n. d.</td><td>n. d.</td><td><= 4%;</td></tr><tr><td>Total Dry</td><td>< 50 mg/l;</td><td>< 50 mg/l;</td><td>< 250mg/l;</td></tr><tr><td>Temperature</td><td>4 -35° C;</td><td>4 -30° C;</td><td>4 - 20 ° C;</td></tr></table> <p>Supply and delivery according to the manufacturers specifications.</p> <p>Product / proof of delivery: LED XL EasyFit 10 Art. 76458</p> <p>OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800 (or equivalent) Entered by the bidder</p>	water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7.2 -7.6	7,2 -7,6	8	Hardness	8 -15 ° DH;	8 -15 ° DH;	20 -30 ° DH;	Free Chlorine	< 0.3 mg/l;	0.3 -0.6 mg/l;	< 0.3 mg/l;	Chlorine	< 250 mg/l;	< 200 mg/l;	<=22000 mg/l;	Salinity	n. d.	n. d.	<= 4%;	Total Dry	< 50 mg/l;	< 50 mg/l;	< 250mg/l;	Temperature	4 -35° C;	4 -30° C;	4 - 20 ° C;		
water-quality-matrix																																							
	Freshwater	Poolwater	Seawater																																				
PH.Value	7.2 -7.6	7,2 -7,6	8																																				
Hardness	8 -15 ° DH;	8 -15 ° DH;	20 -30 ° DH;																																				
Free Chlorine	< 0.3 mg/l;	0.3 -0.6 mg/l;	< 0.3 mg/l;																																				
Chlorine	< 250 mg/l;	< 200 mg/l;	<=22000 mg/l;																																				
Salinity	n. d.	n. d.	<= 4%;																																				
Total Dry	< 50 mg/l;	< 50 mg/l;	< 250mg/l;																																				
Temperature	4 -35° C;	4 -30° C;	4 - 20 ° C;																																				