



	Fresh Water	Pool Water	Sea Water	220-240 V	400 V	110-120 V	50 Hz	60 Hz	12 V AC	24 V DC	DMX	DMX/RDM	Plug and Spray
DMX-connection cable													
DMX-Box /01													

## DMX-CONNECTION CABLE AND DMX-Box /01

OASE connection cable DMX /01 cables are designed specially for underwater applications.

The unique connection sockets based on XLR standards (5-pole) are IP 68 rated. The gaskets are integrated in the plugs.

### Product characteristics at a glance

- Female / male connections
- IP 68 rated
- 2-core shielded
- DMX/RDM capable

The DMX-Box /01 is for the connection of DMX cable.

The DMX-Box /01 can be used for Extensions of DMX cable.

### Product characteristics at a glance

- Female / male connection
- IP 68 rated
- DMX/RDM capable



Connection cable DMX



DMX-Box /01



## The World's first IP 68 underwater cable connection technology.

An optimally coordinated and patented connection technology: The axial flat seal with integrated capillary lock of the cable guarantee a transverse and longitudinal water tightness of both the connectors and the associated connection boxes (DMX box) up to a depth of 4 metres.











The IP 68 connection technology not only ensures long-lasting safety but it is also very easy to install. No more cumbersome and insecure wiring by an electrician at the construction site. Thus as a complete system can be easily assembled from our diver-

se range of pumps, LED lighting, JumpingJets and many more together with our IP 68 pluggable cables and power supplies. The 24 V plug is mechanically protected against polarity reversal. This prevents short circuits by interchanged contacts.

### Accessories (must be ordered separately)

Power splice 20	57648
-----------------	-------

Distance piece with blind caps	46230
--------------------------------	-------

Connection cable DMX /01	1.0 m	1.5 m	3.0 m	5.0 m	10.0 m	20.0 m	End resistant for BUS-system DMX /01	DMX-Box /01
 								
Connection cable DMX /01	1.0 m	1.5 m	3.0 m	5.0 m	10.0 m	20.0 m	End resistant for BUS-system DMX /01	DMX-Box /01
Length [m]	1.0	1.5	3.0	5.0	10.0	20.0	—	—
Cable diameter [mm²]	2 x 0.34	2 x 0.34	2 x 0.34	2 x 0.34	2 x 0.34	2 x 0.34	—	—
Weight [kg]	0.1	0.2	0.3	0.4	0.6	1.1	0.1	0.1
Order no.	12368	49628	12369	12371	12372	12373	12007	57646