

01 Specs 01Title	Comet 15 - 20 T			01.09.16 AO VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit			Unit price	Total price																																				
01.1 Position	<p>Description: Clear stream single jet nozzle made of brass.</p> <p>Installation and operation in freshwater.*</p> <p>Technical data: Dimensions (Ø x H): 63,3 x 152 [mm] Material: brass Weight: 0,86 kg Effect height: 0,5 - 14,0 [m] Nozzle diameter at orifice: 20 mm Adjustable angular range: 15° Water-level independent: yes</p> <p>Double nipple: Material: brass Integrated flow rectifier: yes Connecting thread (Outside thread): G1 1/2</p> <p>Union nut: Material: brass Chamfered: yes Connecting thread (Inner thread): G1 1/2 Wrench size: AF55</p> <p>* <table border="1" data-bbox="300 1104 1214 1603"> <thead> <tr> <th colspan="4" data-bbox="300 1104 1214 1133">water-quality-matrix</th> </tr> <tr> <th data-bbox="300 1133 461 1164"></th> <th data-bbox="461 1133 719 1164">Freshwater</th> <th data-bbox="719 1133 978 1164">Poolwater</th> <th data-bbox="978 1133 1214 1164">Seawater</th> </tr> </thead> <tbody> <tr> <td data-bbox="300 1164 461 1234">PH.Value</td> <td data-bbox="461 1164 719 1234">7,2 -7,6</td> <td data-bbox="719 1164 978 1234">7,2 -7,6</td> <td data-bbox="978 1164 1214 1234">8</td> </tr> <tr> <td data-bbox="300 1234 461 1303">Hardness</td> <td data-bbox="461 1234 719 1303">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="719 1234 978 1303">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="978 1234 1214 1303">20 -30 ° DH; 356 - 534 ppm CaCo3</td> </tr> <tr> <td data-bbox="300 1303 461 1361">Free Chlorine</td> <td data-bbox="461 1303 719 1361">< 0,3 mg/l; < 0,036 moz/gal</td> <td data-bbox="719 1303 978 1361">0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td data-bbox="978 1303 1214 1361">< 0,3 mg/l; < 0,036 moz/gal</td> </tr> <tr> <td data-bbox="300 1361 461 1420">Chlorine concentration</td> <td data-bbox="461 1361 719 1420">< 250 mg/l; < 30,28 moz/gal</td> <td data-bbox="719 1361 978 1420">< 200 mg/l; < 24,2 moz/gal</td> <td data-bbox="978 1361 1214 1420"><=22000 mg/l; <=2664 moz/gal</td> </tr> <tr> <td data-bbox="300 1420 461 1478">Salinity</td> <td data-bbox="461 1420 719 1478">n. d.</td> <td data-bbox="719 1420 978 1478">n. d.</td> <td data-bbox="978 1420 1214 1478"><= 4%; <= 40.000 ppm</td> </tr> <tr> <td data-bbox="300 1478 461 1536">Total Dry Residue</td> <td data-bbox="461 1478 719 1536">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="719 1478 978 1536">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="978 1478 1214 1536">< 250mg/l; < 30,28 moz/gal</td> </tr> <tr> <td data-bbox="300 1536 461 1603">Temperature</td> <td data-bbox="461 1536 719 1603">4 -35° C; 39 - 95 ° F</td> <td data-bbox="719 1536 978 1603">4 -30° C; 39 - 86 ° F</td> <td data-bbox="978 1536 1214 1603">4 - 20 ° C; 39 - 68 ° F</td> </tr> </tbody> </table> </p>			water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																									
	Freshwater	Poolwater	Seawater																																						
PH.Value	7,2 -7,6	7,2 -7,6	8																																						
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																						
<p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery: Comet 15 - 20 T Art. 50971</p> <p>OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800</p> <p>(or equivalent) Entered by the bidder</p>																																									