

OASE GmbH
 Tecklenburger Straße 161
 D - 48477 Hörstel
 Phone: +49(0)54 54 – 800
 Fax: +49(0)54 54 – 80 322
 info@oase.com
 www.oase-professional.com

ProfiLux Basic LED XL RGBW Spot / DMX/02



70134


Fresh water	Pool water	Sea water	220-240 V	400 V	110-120 V	50 Hz	60 Hz	12 V AC	24 V DC	DMX	DMX/RDM	Plug & Spray

Product characteristics at glance




- Energy efficient LED-RGBW spotlight with mounting bracket and fine adjustment.
- Power consumption only 20.4 W
- Temperature controlled LED
- 1263 Lumen with a narrow beam angle of 11°
- Dimensions lamp housing: (Ø x h) 198 x 156 [mm]
- Wet and dry installation - waterproof IP 68; 2m
- For fresh water and pool water
- External electronic in a separate control box / junction box – waterproof connector, easy to connect.
- Controllable and DMX/RDM capable with Underwater LED Driver
- Colour temperature of the white LEDs: 4000 K
- Individual measurement of the basic colours if the LED-RGBW lights and the use of the Underwater LED Driver/DMX/02 guarantees equal brightness of all lights in the system and a homogeneous colour combination
- Galvanic isolation between the DMX and 24V DC power
- Lifetime: 50.000*

*In case of underwater application, an intelligent heat management and quality LED enables a lifetime of up to 50.000 hrs.



The information contained in this data sheet is the sole property of OASE GmbH. Any reproduction in part or as a whole without the written permission of OASE GmbH is prohibited.



System drawing:



No.	Cable	Possible length
1	Power cable 24V DC	1 m / 1.5m / 3 m / 7.5 m / 15 m
2	DMX cable	1 m / 1.5m / 3 m / 5 m / 10 m / 20 m
3	Hybrid extension cable	3 m / 7.5 m



70134

Diagram RGBW all on; 1263 lm (80m / 20m)





70134

Diagram red; 284 lm (80m / 20m)




70134

Diagram green; 509 lm (80m / 20m)




70134

Diagram blue; 156 lm (80m / 20m)





Distance [m] Cone Diameter [m] Illuminance [lx]
 — C0 - C180 (Half-value Angle: 10.4°)



Distance [m] Cone Diameter [m] Illuminance [lx]
 — C0 - C180 (Half-value Angle: 10.4°)

70134

Diagram only white; 313 lm (80m / 20m)



OASE GmbH
 Tecklenburger Straße 161
 D - 48477 Hörstel
 Phone: +49(0)54 54 – 800
 Fax: +49(0)54 54 – 80 322
 info@oase.com
 www.oase-professional.com

ProfiLux Basic LED XL RGBW Spot / DMX/02



70134

ProfiLux Basic LED XL RGBW Spot / DMX/02		
Luminous flux all on	lm	1263
Luminous flux red	lm	284
Luminous flux green	lm	509
Luminous flux blue	lm	156
Luminous flux white	lm	313
Colour temperature LED white	K	4000 (± 200)
Colour Rendering Index (CRI)	%	80
Beam angle	°	11 (± 2)
Strobe effect	Hz	25
Weighted energy consumption	kWh/1000h	22,4
Rated voltage	V/DC	24
Power consumption	W	20.4
Rated current	A	1.18
Dim frequency	Hz	2800
Power connection type		Hybrid Socket
Protection class		IP 68/2m
Dimensions (Ø x h)	mm	198 x 156
Material		stainless steel 1.4301 (AISI 304)
Weight	kg	2.1
Order no.		70134