

01 Specs 01Title	Comet 5 - 10 Silver			01.09.16 AO VS.02	Project No.
Item / No.	Description / Quantity / Unit			Unit price	Total price
01.1 Position	<p>Description: Clear stream nozzle made of chromed and nickel plated brass.</p> <p>Installation and operation in freshwater.*</p> <p>Technical data: Dimensions (Ø x H): 28 x 87 [mm] Material: double coated brass Weight: 0,13 kg Effect height: 0,5 - 6,0 [m] Nozzle diameter at orifice: 10 mm Adjustable angular range: 15° Water-level independent: yes</p> <p>Double nipple: Material: double coated brass Integrated flow rectifier: yes Connecting thread (Outside thread): G1/2</p> <p>Union nut: Material: double coated brass Chamfered: yes Connecting thread (Inner thread): G1/2 Wrench size: AF24</p> <p>*</p>				
water-quality-matrix					
	Freshwater	Poolwater	Seawater		
PH.Value	7,2 -7,6	7,2 -7,6	8		
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3		
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal		
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal		
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm		
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal		
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
Supply and delivery according to manufacturer specifications.					
Product / proof of delivery:					
Comet 5 - 10 Silver					
Art. 50722					
OASE GmbH					
Tecklenburger Str. 161					
48477 Hörstel / Germany					
Phone: +49 5454 800					
(or equivalent)					
.....					
Entered by the bidder					