

01 Specs 01Title	ProfiLux LED L RGB Spot / DMX / 02			12.11.19 MH VS.01	Project No.																																					
No / Art.	Description / Quantitiy / Unit			Unit price	Total price																																					
	* <table><tr><th colspan="4">water-quality-matrix</th></tr><tr><th></th><th>Freshwater</th><th>Poolwater</th><th>Seawater</th></tr><tr><td>PH.Value</td><td>7,2 -7,6</td><td>7,2 -7,6</td><td>8</td></tr><tr><td>Hardness</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>20 -30 ° DH; 356 - 534 ppm CaCo3</td></tr><tr><td>Free Chlorine</td><td>< 0,3 mg/l; < 0,036 moz/gal</td><td>0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td><td>< 0,3 mg/l; < 0,036 moz/gal</td></tr><tr><td>Chlorine concentration</td><td>< 250 mg/l; < 30,28 moz/gal</td><td>< 200 mg/l; < 24,2 moz/gal</td><td><=22000 mg/l; <=2664 moz/gal</td></tr><tr><td>Salinity</td><td>n. d.</td><td>n. d.</td><td><= 4%; <= 40.000 ppm</td></tr><tr><td>Total Dry Residue</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 250mg/l; < 30,28 moz/gal</td></tr><tr><td>Temperature</td><td>4 -35° C;</td><td>4 -30° C;</td><td>4 - 20 ° C;</td></tr></table>				water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C;	4 -30° C;	4 - 20 ° C;		
	water-quality-matrix																																									
		Freshwater	Poolwater	Seawater																																						
	PH.Value	7,2 -7,6	7,2 -7,6	8																																						
	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
	Temperature	4 -35° C;	4 -30° C;	4 - 20 ° C;																																						
	** only in conjunction with the Underwater LED driver																																									
	DMX RDM [Remote D evice M anagment] is a bidirectional bus for querying and programing of DMX-devices. A RDM control unit is capable of identifying connected devices and to -partial automatically- configure them. DMX RDM devices can be operated simultaneously with simple DMX devices at the same time.																																									
	Supply and delivery according to the manufacturers specifications.																																									
	Product / proof of delivery: ProfiLux LED L RGB Spot / DMX / 02 Art. 36088																																									
	OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800 (or equivalent) Entered by the bidder																																									